

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

ELEGANCE SILK

Description and Application

CATEGORY

Wall Coating

DESCRIPTION

Elegance Silk is a high quality, enviro-friendly exterior wall coating, designed and formulated (to Grade 1 specifications) using quality raw materials to combat South-Africa's extreme climatic conditions. It is also user-friendly (almost zero spatter, low odour and easy to apply). Elegance Silk has an elegant, silk finish.

FEATURES

1. Resistance to UV (Sun) passes 1 500-hour SABS Test
2. Excellent Flexibility
3. Stain resistant. Now will resist even hydrocarbon staining.
4. Non-Yellowing
5. Mould resistance
6. Low Odour
7. Covers hairline cracks
8. Waterproofs vertical surfaces
9. Elegance washes easily (dust removed simply by rinsing with a hose pipe).
10. Almost zero roller spatter on application.
11. Available in any colour.
12. Elegance Silk can be used over Paintcor AquaMatt or AquaSeal waterproofing systems as a maintenance coat to extend guarantee periods and will allow for a wider choice of colours.
13. Adhesion promoted: It can be applied to a whole range of surfaces like:
 - Old enamel – sand first
 - Certain plastics – clean first (Garden Furniture)
 - Bathrooms

AREAS OF USE

- Interior and Exterior Walls
- Flat Deck Roofs
- Kitchens and Bathrooms

PAINTCOR

SUPREME QUALITY *Since 1986*

SURFACE PREPARATION AND APPLICATION

New Plaster

1. Remove all loose friable material.
2. If the plaster is porous and/or under bound then apply 1 coat of Paintcor's AcrySeal Acrylic Sealer diluted 1:1 with water. Allow to dry, then if necessary, apply 1 coat of Paintcor's AcrylUnder and allow to dry.
3. If plaster is of good quality then apply 1 coat of Paintcor's Plaster Prime. Allow to dry followed by 1 coat of AcrylUnder if necessary. Allow to dry. (please see note)
4. Finally apply at least 2 coats of Elegance Silk at a spread rate of no more than 10 meters square per litre per coat. Allow to dry between coats.

Old Plaster

1. Check adhesion of existing paint. (Cross hatch adhesion test). Using a Stanley knife, cut through the paint surface to the substrate vertically and horizontally approximately 3mm apart, creating little squares. If the edges of the squares curl up, and the square can easily be removed, this means the adhesion of the old paint system is failing. If the paint system is failing, remove all old paint back to a sound surface.
2. Apply 1 coat of Paintcor's AcrySeal Acrylic Sealer diluted 1:1 with water to all areas to be painted (if old paint system was failing) Allow to dry. Apply 1 coat of Paintcor's AcrylUnder (if necessary). Allow to dry. (please see note)
3. If paint system is in good condition, wash down walls to remove dirt and dust. Allow to dry.
4. Finally apply at least two coats of Paintcor's Elegance Silk at a spread rate of no more than 10 square meters per litre per coat. Allow to dry between coats.

Note: AcrylUnder is only necessary after priming or sealing plaster if plaster texture is a problem. Paintcor's SubTex or RippleTex can also be used to correct major plaster texture differences before application of top coats.

PAINTCOR

SUPREME QUALITY *Since 1986*

APPLICATION EQUIPMENT

Apply by Brush, Sheepskin/Synthetic Roller or Spray

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

STORAGE

Keep stored in cool, dry conditions and away from children.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1585
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED

