

[Type here]

PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

FLASHPATCH INTERIOR

Description and Application

CATEGORY

Patching Compound

DESCRIPTION

FlashPatch Interior is a resin-bound crack-filler, designed for interior use. Proper application will result in a smooth white finish, optimising the application of top coats.

FEATURES

- Dries to a white, tough, smooth and durable finish with good adhesion.
- It can be sanded easily.
- No primer is required before painting.
- Supplied ready for use.

AREAS OF USE

- Filling Interior cracks
- Filling Interior holes

SURFACE PREPARATION AND APPLICATION

1. Ensure the cracks or holes are clean, dry and free of loose or friable material.
2. If the plaster work is poor / friable, apply one coat of Paintcor's AcrySeal acrylic sealer diluted 1:1 with water to the crack before filling. Allow 30 minutes @ 25 degrees C to dry
3. Using a spatula or scraper, fill the voids with Paintcor's FlashPatch interior, filling the crack with a little more FlashPatch than seemingly necessary.
4. Allow sufficient time to dry to a hard finish.
5. Sand the surface down to a smooth, white finish level with the surface applied to.
6. Remove sanding dust.
7. Apply two top coats of any acrylic top coat of your choice. Allow drying between coats.
8. It is not necessary to prime FlashPatch crack filler before painting.

NOTE: FlashPatch Interior must not be applied at more than 5mm wet film per application.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311

Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za

Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955

Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED



[Type here]

PAINTCOR

SUPREME QUALITY *Since 1986*

APPLICATION EQUIPMENT

Scraper / Putty Knife

CLEANING EQUIPMENT

Clean all equipment with water immediately after use.

STORAGE

Keep stored in cool, dry conditions and away from children.

Paintcor cc
Reg No: CK 86/19456/23
VAT No: 4830119311
Members: G. Williams, G. Adendorff
W. Williams

Head office: 1494 Mailship
street, Laser Park, Honeydew, 2040
Postal Address: P.O. Box 917,
Northriding, 2162
RSA

Email
sales@paintcor.co.za
Website
www.paintcor.co.za

Tel: 011 794 2885
Fax no: 011 794 6955
Emergency Numbers
+27(0) 79 526 1565
+27(0) 84 305 5636



SABS
ISO 9001 CERTIFIED

