

# PAINTCOR

SUPREME QUALITY *Since 1986*

2020 Revision

## FLASHPATCH INTERIOR

### Technical Specifications

Vehicle Type	Modified Acrylic
Solvent	Water
Enviro Rating	27.8g/L of VOC (Conforms to E.U 2010 VOC rules)
Dilution / Thinning	Supplied ready for use
Theoretical Spread Rate	N/A
Apply with	Spatula, Trowel, Scraper
Drying time	@ 25°C - 1 hour @ 2mm thick
Wash ability	N/A
Elongation	N/A
Pigment	White
Solids Volume	62%
Flexibility	N/A
Colour	White
Finish	Smooth
Storage	Cool, dry place.
Over coating	Undercoat or top coat of your choice
Packaging	250ml, 500ml, 1L, 5L and 20L
Guarantee	N/A
Conditions of Guarantee	N/A
Resistance to Water	Fair
Resistance to Solvents	Poor
Impact Resistance	N/A
Active Ingredient	N/A
Additional Amount	N/A
Caution	Safe, Non-toxic, Non-flammable
Catalyst Ratio	N/A
Recommended Dry Film	3 to 4mm
Freeze Thaw	Pass
Accelerated Stability	Pass
Accelerated Weathering	N/A
Appearance	Thick, white paste

**Note:** *FlashPatch Interior is for Interior use only. VOC's are calculated on specific raw materials used in the product which contain VOC's, namely Glycol, Amine and free monomers.*

# PAINTCOR

SUPREME QUALITY *Since 1986*

**Paintcor cc**  
Reg No: CK 86/19456/23  
VAT No: 4830119311  
**Members:** G. Williams, G. Adendorff  
W. Williams

**Head office:** 1494 Mailship  
street, Laser Park, Honeydew, 2040  
**Postal Address:** P.O. Box 917,  
Northriding, 2162  
RSA

**Email**  
[sales@paintcor.co.za](mailto:sales@paintcor.co.za)  
**Website**  
[www.paintcor.co.za](http://www.paintcor.co.za)

**Tel:** 011 794 2885  
**Fax no:** 011 794 6955  
**Emergency Numbers**  
+27(0) 79 526 1585  
+27(0) 84 305 5636



**SABS**  
ISO 9001 CERTIFIED

